

Triumph®

by IDEAL

→ 4215 SEMI-AUTOMATIC CUTTER WITH DIGITAL DISPLAY

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | patented, lever-activated, fast-action clamp | side guide with measuring scale | spindle-guided back gauge with calibrated crank | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | optional stand (shown) or cabinet

Dimensions (D x W x H): 27 ¼ x 25 ¼ x 14 ½ inches (41 ½ H with stand, 42 ½ H with cabinet),
Shipping weight: 191 lbs. (217 with stand, 278 with cabinet).



FRONT SAFETY GUARD



The hinged, transparent front safety guard is electronically controlled.

DIGITAL DISPLAY



A digital measurement readout ensures exact positioning of back gauge.

FRONT BLADE CHANGE



The blade changing device covers edge of blade for safe handling.

→ TRIUMPH 4215

Cutting width	16 7/8"
Cutting height	1 1/2"
Narrow cut	1 3/8"
Cutting length behind blade	15 5/8"
Table length in front of blade	9"
Motor	3/5 hp
Power supply	115 V, 60 Hz

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com